


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A63B 59/14	A1	(11) International Publication Number: WO 95/01820 (43) International Publication Date: 19 January 1995 (19.01.95)
(21) International Application Number: PCT/FI94/00318 (22) International Filing Date: 8 July 1994 (08.07.94) (30) Priority Data: U930387 8 July 1993 (08.07.93) FI (71)(72) Applicant and Inventor: PESONEN, Leo [FI/FI]; Pallokuja 2 as 12, FIN-01280 Vantaa (FI). (74) Agents: LAINEN, Seppo et al.; Seppo Laine Oy; Lönnrotinkatu 19 A, FIN-00120 Helsinki (FI).	(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, ES, FI, GB, GE, HU, JP, KE, KG, KP, KR, KZ, LK, LT, LU, LV, MD, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SI, SK, TJ, TT, UA, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD). Published <i>With international search report.</i>	

(54) Title: ICE-HOCKEY STICK

(57) Abstract

In this document is described an ice-hockey stick comprising an essentially straight stick shaft (1) and a blade (2) attached to the lower end of the shaft and sideways aligned to an angle relative to the shaft. According to the invention the stick includes at least one oblong reinforcement part (4, 5) extending from the center toward each stick shaft end, with a cross section diminishing toward the ends of the stick shaft (1), whereby the stiffness of stick shaft (1) is variable in the longitudinal direction of the stick shaft so that the stiffest area of the stick shaft (1) is approximately at the midpoint of the shaft (1), that is, the lower hand grip point of the player using the stick, and the shaft stiffness diminishes from the grip point toward the ends of the stick shaft.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LU	Luxembourg	SN	Senegal
CN	China	LV	Latvia	TD	Chad
CS	Czechoslovakia	MC	Monaco	TG	Togo
CZ	Czech Republic	MD	Republic of Moldova	TJ	Tajikistan
DE	Germany	MG	Madagascar	TT	Trinidad and Tobago
DK	Denmark	ML	Mali	UA	Ukraine
ES	Spain	MN	Mongolia	US	United States of America
FI	Finland			UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

Ice-hockey stick

The present invention is related to an ice hockey stick according to the preamble of the claim 1.

5

Several different methods of striking the puck are used in the game of ice-hockey. The highest speed for the puck is attained by a slap shot in which the player's lower hand holding the stick at its lower part and stick are rotated at the side of the player's body behind the body, and the puck is then shot vigorously forward by rotating the body and simultaneously sending the lower hand with the stick energetically forward. In this manner the puck is accelerated by the stick blade at an extremely high speed in a successful shot, and the puck is provided with a maximum speed, thereby giving the goalkeeper a minimum time to react to the approaching puck.

15

The flexibility of the stick shaft is extremely important for attaining a powerful shot. When the stick blade hits the puck, the blade is bent backward and the stick shaft is flexed forward at the player's lower hand. As the shafts of conventional sticks have a constant cross section over the entire length of the stick shaft, and consequently, a constant stiffness, the stick is obviously flexed maximally at the player's lower hand which pushes the stick forward. However, such a function of the stick fails to impart maximum energy to the shot. As the maximum deflection of the stick shaft occurs at the midpoint of the shaft, the ends of the stick shaft remain almost unbent, whereby the elasticity of the whole stick shaft length remains marginally utilized in the shot. Thus, a portion of the shot input energy is consumed in bending the shaft and thus will not contribute to the puck speed as it leaves the stick blade.

It is an object of the present invention to achieve an ice-hockey stick suited to impart a maximum acceleration to the puck in a slap shot through improved utilization of the elasticity of the stick shaft.

30

The invention is based on designing the stick shaft stiffness to be nonconstant so that the highest stiffness of the shaft coincides at least essentially with the lower hand of the player using the stick and then fall off toward the lower shaft end or both shaft ends.

5

More specifically, the ice-hockey stick according to the invention is characterized by what is stated in the characterizing part of the claim 1.

The invention offers significant benefits.

10

By virtue of the present invention, the energy imparted by the player to the shot is utilized to a greater degree than in the prior art. In fact, the stick shaft can be made almost inflexible at the grip of the player's lower hand, whereby the stick ends obviously bend more than in the prior art, and the stick shaft acts as a bow.

15

However, in practice the stick shaft is stiffened only so much that the deflection of the stick shaft is as constant as possible over the entire length of the shaft.

20

When the puck leaves the blade, the spring-like shaft effectively converts the energy used for bowing the shaft into the translational energy of the puck, thus imparting maximum possible initial speed for the puck. The flexible part of the stick shaft becomes longer owing to the more homogeneous distribution of the shaft deflection over its entire length, whereby its total permissible deflection becomes larger. Though the shaft is designed for a nonconstant stiffness, its fabrication cost will not be appreciably higher than that of a conventional stick.

25

The external dimensions and outlook of the stick can be kept identical to that of the prior-art sticks, thus obviating the need for the players to spend time for getting accustomed with the novel stick shaft, whereby the acceptance threshold for the novel stick will be low.

30

In the following the invention will be examined in more detail with reference to the attached drawing, in which:

Figure 1 is a side view of an embodiment of the ice-hockey stick according to the invention shown with the stick reinforcements;

5 Figure 2 is a view of the stick illustrated in Fig. 1 shown from the direction of the stick blade;

Figure 3 is a cross section of the stick shaft; and

10 Figure 4 is an assembly diagram for the different elements of the stick shaft according to the invention.

The stick shaft can be fabricated starting from a core 3 of the stick made by, e.g., gluing from wood or plywood, and then applying the reinforcement plies onto the core by gluing. A suitable thickness for the core is approx. 17 mm, since
15 the target thickness for a finished shaft is 20 mm with a rectangular cross section of approx. 20 mm by 30 mm. Onto the shaft blank thus fabricated is next laminated by gluing a reinforcement part 4, 5 comprising a center part as wide as the shaft 1 and wing parts linearly tapering from the center part. The length of the center part 4 is 200 - 300 mm, and the wing parts 5 are designed so tapering
20 that their total length from the end of the center part to the tip of the wing-part is 200 - 300 mm. The reinforcement is glued onto the shaft blank 1 so that its center 4 is coincident with the grip position of the player's lower hand. In practice the center of a reinforcement in a stick of 1400 mm length is placed to approx. 700 mm from the heel joint between the blade 2 and the shaft 1. The
25 location of the reinforcement center point may, and in fact, should be aligned exactly to the normal grip point of each individual player. After the gluing step of the reinforcement 4, 5, complementary pieces 6, 7 with a thickness identical to that of the reinforcements are laminated to the stick shaft ends, whereby the complementary pieces must be designed to have a forked end complementary to
30 the shape of the tip 5 of the reinforcements 4, 5. Now the shaft 1 is brought to a

constant thickness permitting an optional, conventional reinforcement ply and a top ply 8 to be glued onto it.

5 The thickness of the reinforcement is approx. 0.5 - 1 mm and the reinforcement is applied at least to the front side of the shaft 1, that is, on that side of the stick where the blade 2 is concave. If a stiffer shaft 1 is desirable, the reinforcement can be applied to both sides of the shaft 1. The material of the reinforcement part 4, 5 can be, e.g., glass fiber or carbon fiber or any other reinforcement material offering sufficient stiffness properties. The complementary pieces 6, 7 to the
10 reinforcement are advantageously of the same material as the stick shaft, whilst their material selection is nonessential to the function of the shaft 1.

With reference to the embodiments illustrated in Figs. 1 - 4, the reinforcement 4, 5 is shuttle-shaped in the side view, and its both wing parts 5 are triangularly
15 tapered to sharp tips. The shape of the wing parts and thus the entire shape of reinforcements can be varied in a wide range. However, it is essential to provide a sufficiently monotonous stiffness change along the length of the stick shaft to avoid the occurrence of an abrupt stiffness discontinuity at which the shaft might break under load. The tips of the reinforcements can alternatively be forked, for
20 example, whereby the tips of the reinforcements and their complementary pieces will have mirrored shapes to those shown in the diagrams. The gradual change of the stick cross section may also be realized advantageously so that, e.g., the thickness of the reinforcement gradually tapers off toward the ends of the stick shaft, whereby the reinforcement can have a constant width over its entire length.
25 Obviously, the shape design of the reinforcement can be implemented in a plurality of manners, and a separate reinforcement piece is not necessarily needed in all embodiments of the invention. Sticks with composite material or aluminum shafts which are emerging on the market can be easily fabricated to have a variable stiffness in accordance with the invention. In practice this can be implemented
30 through, e.g., varying the thickness of the shaft tube wall or the reinforcement structure of a composite material stick. In these cases the reinforcement part is an

integral part of the shaft material and no separate reinforcement part can be indicated. Manufacture of metal tubes having a constant external diameter and a varying inner diameter is known per se and these kind of tubes are used for example in bicycle frames. A composite structure offers a wide variety of possibilities. Properties of a composite structure can be varied by changing the amount or material of reinforcement fibres. In a composite structure dimensions of the structure do not alone characterise the properties of the structure and for example, the flexibility of a composite shaft depends mainly of the volume and properties of the reinforcement material in a given cross section. Advantageously, the external cross-sectional dimensions of the stick shaft are maintained constant over the entire length of the stick shaft, whilst in special cases also a stick with the thicker cross section at the player's grip point is feasible. However, since a variable stick shaft thickness may feel odd to the players, a stick with a constant cross section must be preferred.

When a conventional reinforcement system of an ice-hockey stick is combined with the embodiment according to the invention, an extremely wide range of stick shaft characteristics in a shot situation can be realized. For the maximum control of the initial energy of the shot it is most advantageous to have a relatively stiff stick shaft which is nonflexible exactly at the grip point of the player's lower hand with a gradually increasing flexibility toward the stick ends. This kind of a stick design makes the stick behave ideally and offers the highest efficiency in converting the energy imparted by the player into the translational energy of the puck. Top players use today custom-made sticks, and by virtue of this invention, a flexible stick compliant with the minutes of the player's preferences can be fabricated in an uncomplicated manner. The flexibility of the stick can be made to vary, e.g., progressively or to be asymmetric relative to the grip point. For example, the flexibility of the shaft can be constant above the grip point and decrease from the grip point towards the blade.

Claims:

1. An ice-hockey stick comprising an essentially straight stick shaft (1) and a blade (2) adapted to the lower end of the shaft and sideways aligned to an angle relative to said stick, c h a r a c t e r i z e d in that said shaft stick (1) includes
5 at least one oblong reinforcement part (4, 5) extending from the center toward each stick shaft end, with a cross section diminishing toward at least the lower end of the stick shaft (1), whereby the stiffness of stick shaft (1) is variable in the longitudinal direction of the stick shaft so that the stiffest area of the stick shaft
10 (1) is situated approximately at the midpoint of the shaft (1), that is, the lower hand grip point of the player using the stick, and the shaft stiffness diminishes from the grip point toward the end of the stick shaft.
2. An ice-hockey stick according to claim 1, c h a r a c t e r i z e d in that the
15 reinforcement part (4, 5) diminishes towards both ends of the shaft (1).
3. An ice-hockey stick according to claim 1 or 2, c h a r a c t e r i z e d in that the shaft (1) is a metal tube having a constant outer diameter and a variable inner
20 diameter.
4. An ice-hockey stick according to claim 1 or 2, c h a r a c t e r i z e d in that the shaft (1) is a composite structure wherein the flexibility of the shaft is varied by changing the reinforcement structure within the shaft (1).
- 25 5. An ice-hockey stick according to claim 1, 2, or 4, c h a r a c t e r i z e d in that the shaft (1) has a variable outer diameter.





FIG. 3




FIG. 4

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6: A63B 59/14-

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6: A63B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE, A1, 3344781 (EXEL OY), 20 June 1984 (20.06.84), page 7, line 12 - page 8, line 6 --	1,4
A	US, A, 3489412 (D.R. FRANCK ET AL), 13 January 1970 (13.01.70), column 1, line 31 - column 2, line 61, figures 2,3a-3c --	1,3,5
A	SE, C, 169928 (L.W.G. MALMBERG), 22 December 1959 (22.12.59), the whole document --	1

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

10 October 1994

21-10-1994

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Jonas Löfgren

Telephone No. +46 8 782 25 00

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US, A, 4172594 (D.A. DIEDERICH), 30 October 1979 (30.10.79), column 1, line 42 - column 2, line 22, figure 3 -----	1

27/08/94

PCT/FI 94/00318

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
DE-A1-	3344781	20/06/84	CA-A-	1219886	31/03/87
			SE-A-	8306624	17/06/84
			SU-A-	1281159	30/12/86

US-A-	3489412	13/01/70	NONE		

SE-C-	169928	22/12/59	NONE		

US-A-	4172594	30/10/79	CA-A-	1072142	19/02/80
			CA-A-	1074824	01/04/80
			US-A-	4134587	16/01/79
			US-A-	4180413	25/12/79
